



### Awning Warranty

Sunbrella® Fabric is warranted for ten years against fade, rot and mildew. Framework is warranted for ten years and the thread has lifetime warranty. We are not responsible to cover damage to the framework or component parts caused by acts of nature, ex. Sharp objects falling on awning, heavy snow loads on awning, hurricane force winds.



*30" Projection*

**Spear Awning**

*Installation  
&  
Product Guide*

1111 S Talbot St.  
St. Michaels, MD 21663  
800-933-6936  
Fax 410-745-2920

<http://www.pycawnings.com/>

## **Installation Instructions**

1. Mount first 2 outside Headrod clamps, at the desired position above the window, 7 inches in from each side of awning width. Mount any additional Headrod clamps, spaced evenly across width of awning.

### **Mount level with window.**

Headrod Clamps must be mounted to wall studs, window header or framing structure as they support the entire weight of the awning.

2. Slip the ring pulleys on the inside hook of each Headrod clamp.
3. Distance from screw hole on Headrod clamp down wall to hinge screw hole is 30 inches.

### **Distance between hinges should same as awning width.**

4. Slide Headrod in Headrod pocket of awning. Loosen wingnuts on Headrod clamp. Insert Headrod into Headrod clamp. Tighten the wingnuts over the fabric.

5. Slip the front bar through pocket on awning. (Some front bars are cut in 2 pieces for shipping, if so, connect with screws to make one length)
6. Connect projection bars to the front bar and wall hinge.
7. Mount cleat where desired.

## **Stringing Instructions**

Starting on either side (where you want to mount the cleat), Tie String around front bar at pocket opening of awning using a slip knot. Run String up through ring pulley and down to cleat. Cut to desired length to wrap around cleat.

Repeat through all pocket openings, running strings up to ring pulleys and then across the top of awning through each ring and down to cleat.