

INSTALLATION INSTRUCTIONS See Videos on our YouTube Channel - PYC Awnings

Installing Headrod Clamps:

1. Install the two outer headrod clamps about 10" in from each side of the curtain at the same mounting point where you measured the top of the curtain. For example: if your curtain is 96" Height/Drop you should mount top of headrod clamp 96" up from floor. Install any additional clamps centered as shown on diagram below.

2. Any headrod or pipe over 90" will be cut into two pieces for shipping purposes. Use the couplings provided to attach each piece of the headrod together, and the pipe.

3. Tie ropes to headrod clamps before hanging curtain. - See Diagram Below

Installing Headrod & Galvanized Pipe:

the curtain.

4. The fiberglass headrod goes through the smaller pocket (top of curtain), and the galvanized pipe goes through the larger pocket above the flap (bottom of curtain). *Galvanized pipe can be slid in pocket after curtain is hung on headrod clamps (step 5) to keep the weight off the curtain

*The Galvanized pipe should be 2" off the floor when lowered. The flap can touch the floor.

5. With fiberglass headrod in pocket, clamp curtain onto headrod clamps leaving wingnuts slightly loose. Slip pulleys onto headrod clamp hooks as shown in diagram below. Tighten wingnuts.

Installing Cleat: 6. Install cleat at desired position, on left or right side of Roller Curtain. Porch Roller Curtains 6' to 8' 11" Wide Stringing Diagram Before hanging curtain, tie ropes onto headrod clamps and let rope drop Ropes going through to floor. Ropes will be labeled single pulley, double pulley etc. Hang pulleys are in front of curtain. Pull rope up in front of curtain under galvanized pipe to the pulley the curtain. directly above. String rope through each pulley across the top and down to the cleat. Repeat for each headrod clamp with pulley. When all ropes are strung, pull ropes taut so curtains roll up evenly. Tie ropes together * Tip- Tie knot close to and cut off any excess. pulley to keep center ropes from drooping Headrod Clamp for Single Pulley Support Only **Double Pulley** Cleat Rope in Front of Curtain Rope Behind Curtain Rope goes under galvanized pipe. Slide Galvanized Pipe Through Pocket Flap 0 Tie-Downs **Tie-Downs** Reverse pulley You will have 2 ropes going layout for cleat on The rope tied to each to cleat. Adjust so curtain opposite side of headrod clamp is behind pulls up evenly then tie curtain.

ropes together.